

REVO-DEKO



■ REVO DEKO (Decorative High Bay Luminaires)

GENERAL FEATURES

BODY	: MATT BLACK PAINTED, DKP SHEET STEEL
REFLECTOR	: HIGH PURITY BRIGHT ANODIZED ALUMINIUM(MIRO4)
DIFFUSOR	: TEMPERED OPAL GLASS COVERED WITH SAFETY FILM
BALLAST	: ELECTRONIC BALLAST
LIGHT SOCKET	: T5 LAMP STANDARD G5 SOCKET
EMC	: LIMITED ELECTROMAGNETIC FIELD
VOLTAGE	: 220-240V
APPLICATIONS	: SURFACE MOUNTED, PENDANT

OPTIONS

EMERGENCY KIT

REVO-DEKO: is designed for decorative applications.

This group of fittings provide elegant look and energy saving at the same time for high ceilings.



OPAL GLASS MODELS IP65

- MN2 1*TL554U-SP/CM LB DK
- MN2 1*TL549U-SP/CM LB DK
- MN2 1*TL535U-SP/CM LB DK
- MN2 1*TL528U-SP/CM LB DK
- MN2 1*TL514U-SP/CM LB DK
- MN2 2*TL554U-SP/CM LB DK
- MN2 2*TL549U-SP/CM LB DK
- MN2 2*TL535U-SP/CM LB DK
- MN2 2*TL528U-SP/CM LB DK
- MN2 2*TL514U-SP/CM LB DK

OPEN FRONT MODELS IP20

- MN2 1*TL554U-SP/OA LB DK
- MN2 1*TL549U-SP/OA LB DK
- MN2 1*TL535U-SP/OA LB DK
- MN2 1*TL528U-SP/OA LB DK
- MN2 1*TL514U-SP/OA LB DK
- MN2 2*TL554U-SP/OA LB DK
- MN2 2*TL549U-SP/OA LB DK
- MN2 2*TL535U-SP/OA LB DK
- MN2 2*TL528U-SP/OA LB DK
- MN2 2*TL514U-SP/CM LB DK

